

TCK

CORUNDUM WHEEL FOR CUTTING STONE



Code	Size [mm]	Max. RPM	Max. peripheral speed [m/s]	Pcs.
TCK-11530(X5)	115x3.0x22	13300	80	50
TCK-12530(X5)	115x3.0x22	12250	80	50
TCK-18030(X5)	125x3.0x22	8600	80	25
TCK-23030(X5)	230x3.0x22	6650	80	25

APPLICATION:

Standard disc (straight, type 41) suitable for cutting of stone, terrazzo, reinforced concrete, ceramic materials. Unique composition of the binding resin and abrasive grains ensures long life of the disc and prevents overheating of the material being cut.

TSL

FLAP DISC FOR STEEL



Code	Size [mm]	Max. RPM	Max. peripheral speed [m/s]	Pcs.
TSL-125040(X5)	125x22/40	12250	80	1
TSL-125060(X5)	125x22/60	12250	80	1
TSL-125080(X5)	125x22/80	12250	80	1
TSL-1250100(X5)	125x22/100	12250	80	1
TSL-1250120(X5)	125x22/120	12250	80	1

APPLICATION:

Flap disc (straight, type 41b) with fiberglass backing plate and hard, strong corundum grain (grain size 40-120). Good grinding and polishing performance. Fiberglass backing ensures consistent grinding until complete wear of the abrasive grain. Prevents material scratching.



CORUNDUM BLADES DISPLAY